

www.coachman.co.uk

Designed and produced by: [www.bluestormdesign.co.uk](http://www.bluestormdesign.co.uk)

## Coachman Specifications 2011



**Coachman Caravan Company Limited**  
Amsterdam Road  
Sutton Fields Industrial Estate  
Hull HU7 0XF

**Telephone:** 01482 839737

**Fax:** 01482 878143

**Email:** [sales@coachman.co.uk](mailto:sales@coachman.co.uk)

**Aftercare Telephone:** 01482 877405

**Aftercare Email:** [aftercare@coachman.co.uk](mailto:aftercare@coachman.co.uk)

**Distinction Quality Style**



This brochure has been designed to provide you with basic information prior to making a purchase decision. Please refer to your dealer for additional information before you buy.

Coachman Caravan Company Limited reserves the right to alter technical specifications, prices and model ranges as materials and conditions demand and can accept no responsibility for discrepancies between these and subsequent models. Household items illustrated in the brochure (e.g. fruit and personal effects) have been used to enhance photography and are not supplied with the caravan. Limitations in the printing process may mean colours are not truly represented.

It should be noted that distributors and dealers are not the agents of Coachman Caravan Company Limited and therefore are not authorised to bind the Company by any specific or implied undertaking or representation.

Please note: Touring caravans are designated by the model year. The model year runs from the 1st September to the 31st August: for example a 2011 year model would have been despatched by the manufacturer no earlier than the 15th August, 2010.

All Coachman models have been certified by the National Caravan Council for compliance with stringent European Standards, British Legislation and industry set Codes of Practice, specifically relating to health and safety issues. The approval process covers the testing and inspection of critical areas of the product from fire safety, weights and dimensions to gas, electrics and ventilation. Every Coachman caravan carries the "NCC Approved Caravan" badge. The NCC also conducts unannounced inspections at the Coachman factory to ensure continued compliance.

NCC Approval gives you peace of mind that your caravan is legal and safe.

The tow cars used in this brochure are for illustration purposes only.

As the owner of a Coachman caravan, you will be automatically entitled to join our Owners' Club. For more information about the Club, please contact: The Membership Officer, Coachman Owners' Club, 49 Regency Gardens, Yardley Wood, Birmingham, B14 4JS or visit their website: [www.coachmanclub.co.uk](http://www.coachmanclub.co.uk)

Photography: [www.markkennett.com](http://www.markkennett.com)

Thanks to Burton Agnes Hall [www.burtonagnes.com](http://www.burtonagnes.com)



**Distinction Quality Style**





# Technical Specifications 2011

Model	640/4	650/4	655/6
<b>Number of Berths</b>	4	4	6
<b>Interior Length</b>	6190 mm / 20' 4"	6190 mm / 20' 4"	6190 mm / 20' 4"
<b>Shipping Length</b>	7965 mm / 26' 2"	7965 mm / 26' 2"	7965 mm / 26' 2"
<b>Overall Width</b>	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"
<b>Overall Height (inc T.V Aerial)</b>	2660 mm / 8' 9"	2660 mm / 8' 9"	2660 mm / 8' 9"
<b>Maximum Headroom</b>	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"
<b>Interior Width</b>	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"
<b>Wheel Rim</b>	5.5J x 14	5.5J x 14	5.5J x 14
<b>Tyre Size</b>	185 / 70 R14 88	185 / 70 R14 88	185 / 70 R14 88
<b>Tyre Pressure (at quoted MTPLM)</b>	35 psi / 2.4 bar	35 psi / 2.4 bar	35 psi / 2.4 bar
<b>Bed Sizes</b>	1 x Single	1 x Single	2 x Single
<b>Option 1</b>	1780 mm x 740 mm (5' 10" x 2' 5") 1 x Single 1640 mm x 740 mm (5' 5" x 2' 5") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")	1780 mm x 740 mm (5' 10" x 2' 5") 1 x Single 1640 mm x 740 mm (5' 5" x 2' 5") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	1860 mm x 740 mm (6' 1" x 2' 5") 2 x Single 1780 mm x 700 mm (5' 10" x 2' 4") 2 x Single Bunks 1700 mm x 610 mm (5' 7" x 2' 0")
<b>Bed Sizes</b>	1 x Double	1 x Double	1 x Double
<b>Option 2</b>	2030 mm x 1360 mm (6' 8" x 4' 6") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")	2030 mm x 1360 mm (6' 8" x 4' 6") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	2030 mm x 1450 mm (6' 8" x 4' 9") 1 x Double 1980 mm x 1340 mm (6' 6" x 4' 5") 2 x Single Bunks 1700 mm x 610 mm (5' 7" x 2' 0")
<b>M.T.P.L.M</b>	1810 kg / 35.6 cwt	1800 kg / 35.4 cwt	1870 kg / 36.8 cwt
<b>Mass in Running Order</b>	1650 kg / 32.5 cwt	1640 kg / 32.3 cwt	1690 kg / 33.3 cwt
<b>Personal Payload</b>	160 kg / 3.1 cwt	160 kg / 3.1 cwt	180 kg / 3.5 cwt
<b>Options Payload</b>	0 kg / 0 cwt	0 kg / 0 cwt	0 kg / 0 cwt
<b>Total / Maximum User Payload</b>	160 kg / 3.1 cwt	160 kg / 3.1 cwt	180 kg / 3.5 cwt
<b>Empty Nose Weight</b>	58 kg / 1.1 cwt	75 kg / 1.5 cwt	49 kg / 1 cwt
<b>Maximum Hitch Weight</b>	100kg / 1.9 cwt	100kg / 1.9 cwt	100kg / 1.9 cwt
<b>Awning Size</b>	1058 cm	1058 cm	1058 cm



# Technical Specifications 2011

Model	460/2	520/4	545/4	560/4
<b>Number of Berths</b>	2	4	4	4
<b>Interior Length</b>	4858 mm / 15' 11"	5514 mm / 18' 1"	5800 mm / 19'	5800 mm / 19'
<b>Shipping Length</b>	6633 mm / 21' 9"	7289 mm / 23' 11"	7575 mm / 24' 10"	7575 mm / 24' 10"
<b>Overall Width</b>	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"
<b>Overall Height (inc T.V Aerial)</b>	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"
<b>Maximum Headroom</b>	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"
<b>Interior Width</b>	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"
<b>Wheel Rim</b>	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15
<b>Tyre Size</b>	185 R14 102	195 / 70 R15 104	195 / 70 R15 104	195 / 70 R15 104
<b>Tyre Pressure (at quoted MTPLM)</b>	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar
<b>Bed Sizes</b>	2 x Single	2 x Single	2 x Single	1 x Single
<b>Option 1</b>	1900 mm x 740 mm (6' 3" x 2' 5")	1900 mm x 740 mm (6' 3" x 2' 5") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	1550 mm x 740 mm (5' 1" x 2' 5") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	1540 mm x 740 mm (5' 1" x 2' 5") 1 x Single 1640 mm x 740 mm (5' 4" x 2' 5") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")
<b>Bed Sizes</b>	1 x Double	1 x Double	1 x Double	1 x Double
<b>Option 2</b>	2030 mm x 1450 mm (6' 8" x 4' 9")	2030 mm x 1450 mm (6' 8" x 4' 9") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	2030 mm x 1130 mm (6' 8" x 3' 8") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	2030 mm x 1220 mm (6' 8" x 4' 0") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")
<b>M.T.P.L.M</b>	1430 kg / 28.1 cwt	1590 kg / 31.3 cwt	1630 kg / 32.1 cwt	1645 kg / 32.4 cwt
<b>Mass in Running Order</b>	1303 kg / 25.6 cwt	1437 kg / 28.3 cwt	1474 kg / 29 cwt	1489 kg / 29.3 cwt
<b>Personal Payload</b>	127 kg / 2.5 cwt	153 kg / 3 cwt	156 kg / 3.1 cwt	156 kg / 3.1 cwt
<b>Options Payload</b>	0 kg / 0 cwt	0 kg / 0 cwt	0 kg / 0 cwt	0 kg / 0 cwt
<b>Total / Maximum User Payload</b>	127 kg / 2.5 cwt	153 kg / 3 cwt	156 kg / 3.1 cwt	156 kg / 3.1 cwt
<b>Empty Nose Weight</b>	46 kg / 0.9 cwt	58 kg / 1.1 cwt	55 kg / 1.1 cwt	55 kg / 1.1 cwt
<b>Maximum Hitch Weight</b>	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt
<b>Awning Size</b>	935 cm	995 cm	1030 cm	1030 cm



# Technical Specifications 2011



# Technical Specifications 2011

Model	460/2	470/2	520/4	545/4	560/4
<b>Number of Berths</b>	2	2	4	4	4
<b>Interior Length</b>	4858 mm / 15' 11"	5000 mm / 16' 5"	5514 mm / 18' 1"	5800 mm / 19'	5800 mm / 19'
<b>Shipping Length</b>	6633 mm / 21' 9"	6775 mm / 22' 3"	7289 mm / 23' 11"	7575 mm / 24' 10"	7575 mm / 24' 10"
<b>Overall Width</b>	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"
<b>Overall Height (inc T.V Aerial)</b>	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"
<b>Maximum Headroom</b>	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"
<b>Interior Width</b>	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"
<b>Wheel Rim</b>	5.5J x 14	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15
<b>Tyre Size</b>	185 R14 102	185 R14 102	195 / 70 R15 104	195 / 70 R15 104	195 / 70 R15 104
<b>Tyre Pressure (at quoted MTPLM)</b>	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar
<b>Bed Sizes</b>	2 x Single	2 x Single	2 x Single	2 x Single	1 x Single
<b>Option 1</b>	1900 mm x 740 mm (6' 3" x 2' 5")	1900 mm x 740 mm (6' 3" x 2' 5")	1900 mm x 740 mm (6' 3" x 2' 5") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	1550 mm x 740 mm (5' 1" x 2' 5") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	1540 mm x 740 mm (5' 1" x 2' 5") 1 x Single 1640 mm x 740 mm (5' 4" x 2' 5") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")
<b>Bed Sizes</b>	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double
<b>Option 2</b>	2030 mm x 1450 mm (6' 8" x 4' 9")	2030 mm x 1450 mm (6' 8" x 4' 9")	2030 mm x 1450 mm (6' 8" x 4' 9") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	2030 mm x 1130 mm (6' 8" x 3' 8") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	2030 mm x 1220 mm (6' 8" x 4' 0") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")
<b>M.T.P.L.M</b>	1420 kg / 28 cwt	1435 kg / 28.2 cwt	1585 kg / 31.2 cwt	1620 kg / 31.9 cwt	1635 kg / 32.2 cwt
<b>Mass in Running Order</b>	1288 kg / 25.4 cwt	1302 kg / 25.6 cwt	1427 kg / 28.1 cwt	1459 kg / 28.7 cwt	1474 kg / 29 cwt
<b>Personal Payload</b>	127 kg / 2.5 cwt	128 kg / 2.5 cwt	153 kg / 3 cwt	156 kg / 3.1 cwt	156 kg / 3.1 cwt
<b>Options Payload</b>	5 kg / 0.1 cwt	5 kg / 0.1 cwt	5 kg / 0.1 cwt	5 kg / 0.1 cwt	5 kg / 0.1 cwt
<b>Total / Maximum User Payload</b>	132 kg / 2.6 cwt	133 kg / 2.6 cwt	158 kg / 3.1 cwt	161 kg / 3.2 cwt	161 kg / 3.2 cwt
<b>Empty Nose Weight</b>	47 kg / 0.9 cwt	53 kg / 1 cwt	56 kg / 1.1 cwt	56 kg / 1.1 cwt	55 kg / 1.1 cwt
<b>Maximum Hitch Weight</b>	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt
<b>Awning Size</b>	935 cm	945 cm	995 cm	1030 cm	1030 cm

1. For 2011 models the method of calculating the MRO and payload figures has changed. Allowances for essential equipment (e.g. gas cylinders) previously allowed for in the user payload are now within the MRO. The provision for a leisure battery has been included within the personal effects payload allowances.

2. Imperial conversions are approximate.

3. Awning dimensions represent the shortest ground to ground awning measurements for 2011 model year Coachman caravans. We do however strongly recommend that you consult your awning supplier before making a purchase as awning manufacturers have different methods of sizing their products.

Model	380/2	450/2	520/4	535/4	550/5	560/4	570/6	640/6	655/6
<b>Number of Berths</b>	2	2	4	4	5	4	6	6	6
<b>Interior Length</b>	4021 mm / 13' 2"	4725 mm / 15' 6"	5478 mm / 18'	5550 mm / 18' 3"	5670 mm / 18' 7"	5850 mm / 19' 2"	5850 mm / 19' 2"	6221 mm / 20' 5"	6221 mm / 20' 5"
<b>Shipping Length</b>	5681 mm / 18' 8"	6385 mm / 20' 11"	7138 mm / 23' 5"	7210 mm / 23' 8"	7330 mm / 24' 1"	7510 mm / 24' 8"	7510 mm / 24' 8"	7881 mm / 25' 10"	7881 mm / 25' 10"
<b>Overall Width</b>	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"
<b>Overall Height (inc T.V Aerial)</b>	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2660 mm / 8' 9"	2660 mm / 8' 9"
<b>Maximum Headroom</b>	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"
<b>Interior Width</b>	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"
<b>Wheel Rim</b>	5.5J x 14	5.5J x 14	6.0J x 15	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15	5.5J x 14	5.5J x 14
<b>Tyre Size</b>	175 R14 99	185 R14 102	195 / 70 R15 104	185 R14 102	195 / 70 R15 104	195 / 70 R15 104	195 / 70 R15 104	185 / 70 R14 88	185 / 70 R14 88
<b>Tyre Pressure (at quoted MTPLM)</b>	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	35 psi / 2.4 bar	35 psi / 2.4 bar
<b>Bed Sizes</b>	2 x Single	2 x Single	2 x Single	1 x Single	2 x Single	1 x Single	2 x Single	2 x Single	2 x Single
<b>Option 1</b>	1860 mm x 740 mm (6' 1" x 2' 5")	1860 mm x 740 mm (6' 1" x 2' 5")	1860 mm x 740 mm (6' 1" x 2' 5") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	1660 mm x 740 mm (5' 5" x 2' 5") 1 x Single 1650 mm x 740 mm (5' 5" x 2' 5") 1 x Double 1980 mm x 1390 mm (6' 6" x 4' 7")	1860 mm x 740 mm (6' 1" x 2' 5") 1 x Double 2030 mm x 1390 mm (6' 8" x 4' 7")	1540 mm x 740 mm (5' 1" x 2' 5") 1 x Single 1640 mm x 740 mm (5' 4" x 2' 5") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")	1740 mm x 740 mm (5' 9" x 2' 5") 1 x Single (rear) 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0")	1860 mm x 740 mm (6' 1" x 2' 5") 1 x Single (rear) 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0")	1860 mm x 740 mm (6' 1" x 2' 5") 2 x Single 1780 mm x 700 mm (5' 10" x 2' 4") 2 x Single Bunks 1700 mm x 610 mm (5' 7" x 2' 0")
<b>Bed Sizes</b>	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double
<b>Option 2</b>	2030 mm x 1440 mm (6' 8" x 4' 9")	2030 mm x 1440 mm (6' 8" x 4' 9")	2030 mm x 1440 mm (6' 8" x 4' 9") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	2030 mm x 1250 mm (6' 8" x 4' 1") 1 x Double 1980 mm x 1390 mm (6' 6" x 4' 7")	2030 mm x 1440 mm (6' 8" x 4' 9") 1 x Single 2030 mm x 1390 mm (6' 8" x 4' 7") 1 x Single Bunk 1950 mm x 610 mm (6' 5" x 2' 0")	2030 mm x 1440 mm (6' 8" x 4' 9") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")	2030 mm x 1320 mm (6' 8" x 4' 0") 1 x Single (rear) 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0")	2030 mm x 1440 mm (6' 8" x 4' 9") 1 x Single (rear) 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0")	2030 mm x 1440 mm (6' 8" x 4' 9") 2 x Single Bunks 1740 mm x 620 mm (5' 9" x 2' 0")
<b>M.T.P.L.M</b>	1235 kg / 24.3 cwt	1380 kg / 27.2 cwt	1555 kg / 30.6 cwt	1490 kg / 29.3 cwt	1630 kg / 32.1 cwt	1600 kg / 31.5 cwt	1635 kg / 32.2 cwt	1760 kg / 34.6 cwt	1775 kg / 34.9 cwt
<b>Mass in Running Order</b>	1107 kg / 21.8 cwt	1245 kg / 24.5 cwt	1393 kg / 27.4 cwt	1327 kg / 26.1 cwt	1456 kg / 28.7 cwt	1434 kg / 28.2 cwt	1449 kg / 28.5 cwt	1570 kg / 30.9 cwt	1585 kg / 31.2 cwt
<b>Personal Payload</b>	118 kg / 2.3 cwt	125 kg / 2.5 cwt	152 kg / 3 cwt	153 kg / 3 cwt	164 kg / 3.2 cwt	156 kg / 3.1 cwt	176 kg / 3.5 cwt	180 kg / 3.5 cwt	180 kg / 3.5 cwt
<b>Options Payload</b>	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt
<b>Total / Maximum User Payload</b>	128 kg / 2.5 cwt	135 kg / 2.7 cwt	162 kg / 3.2 cwt	163 kg / 3.2 cwt	174 kg / 3.4 cwt	166 kg / 3.3 cwt	186 kg / 3.7 cwt	190 kg / 3.7 cwt	190 kg / 3.7 cwt
<b>Empty Nose Weight</b>	41 kg / 0.9 cwt	40 kg / 0.8 cwt	47 kg / 0.9 cwt	68 kg / 1.3 cwt	58 kg / 1.1 cwt	40 kg / 0.8 cwt	54 kg / 1.1 cwt	45 kg / 0.9 cwt	56 kg / 1.1 cwt
<b>Maximum Hitch Weight</b>	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt
<b>Awning Size</b>	840 cm	913 cm	992 cm	998 cm	1010 cm	1024 cm	1024 cm	1065 cm	1065 cm