



This brochure has been designed to provide you with basic information prior to making a purchase decision. Please refer to your local dealer for additional information before you buy. Coachman Caravan Company Limited reserves the right to alter technical specifications, prices and model ranges as materials and conditions demand and can accept no responsibility for discrepancies between these and subsequent models. Household items illustrated in the brochure (e.g. fruit and personal effects) have been used to enhance photography and are not supplied with the caravan. Limitations in the printing process may mean colours are not truly represented. It should be noted that distributors and dealers are not the agents of Coachman Caravan Company Limited and therefore are not authorised to bind the Company by any specific or implied undertaking or representation. Please note: Touring caravans are designated by the model year. The model year runs from the 1st September to 31st August: for example a 2009 year model would have been despatched by the manufacturers no earlier than 15th August 2008. All Coachman models have been certified by the National Caravan Council for compliance with stringent European Standards, British Legislation and industry set Codes of Practice, specifically relating to health and safety issues. The approval process covers the testing and inspection of critical areas of the product from fire safety, weights and dimensions to gas, electrics and ventilation. Every Coachman caravan carries the 'NCC Approved Caravan' badge. The NCC also conducts unannounced inspections at the Coachman factory to ensure continued compliance. NCC Approval gives you peace of mind that your caravan is legal and safe.

The tow cars used in this brochure are for illustration purposes only.

As the owner of a Coachman caravan, you will be automatically entitled to membership of our Owners Club. For more information about the Club, please contact: The Secretary, Coachman Owners' Club, 2 Braemar Rise, South Hiendley, Barnsley, South Yorkshire S72 9DJ or visit their website: www.coachmanclub.co.uk

feelthedifference



The Touring Caravan



Coachman Caravan Company Limited

Amsterdam Road, Sutton Fields Industrial Estate,

Hull HU7 0XF Tel: 01482 839737

Aftercare: 01482 877405 www.coachman.co.uk

2009 Specifications



TECHNICAL SPECIFICATIONS 2009

MODEL	640/4	645/4	650/4	655/6
Number of Berths	4	4	4	6
Interior Length	6190mm / 20' 4"	6190mm / 20' 4"	6190mm / 20' 4"	6190mm / 20' 4"
Shipping Length	7965mm / 26' 2"	7965mm / 26' 2"	7965mm / 26' 2"	7965mm / 26' 2"
Overall Width	2260mm/7'5"	2260mm/7'5"	2260mm/7'5"	2260mm/7'5"
Overall Height (inc TV Aerial)	2735mm / 9'	2735mm / 9'	2735mm / 9'	2735mm / 9'
Maximum Headroom	1955mm / 6' 5"	1955mm / 6' 5"	1955mm / 6' 5"	1955mm / 6' 5"
Interior Width	2110mm / 6' 11"	2110mm / 6' 11"	2110mm / 6' 11"	2110mm / 6' 11"
Wheel Rim	5.5J x 14	5.5J x 14	5.5J x 14	5.5J x 14
Tyre Size	175/65 R14 86	175/65 R14 86	175/65 R14 86	175/65 R14 86
Tyre Pressure (at quoted MTPLM)	44 psi / 3 bar	44 psi / 3 bar	44 psi / 3 bar	44 psi / 3 bar
Bed Sizes mm	2 x Single Combined in 'L' shape 1 x Double 1870 x 1370 (6'2" x 4'6")	2 x Single Combined in 'L' shape 2 x Single 1910 x 760 (6'3" x 2'6") 1880 x 760 (6'2" x 2'6")	2 x Single 1880 x 720 (5'11" x 2'4") 1680 x 720 (5'6" x 2'4") 1 x Double 1850 x 1370 (6'1" x 4'6")	2 x Single 1880 x 720 (6'2" x 2'4") 2 x Single 1830 x 720 (6'0" x 2'4") 2 x Single Bunk 1730 x 610 (5'8" x 2'0")
Option 1				
Bed Sizes mm	1 x Double 2030 x 1320 (6'8" x 4'4") 1 x Double 1870 x 1370 (6'2" x 4'6")	1 x Double 2030 x 1320 (6'8" x 4'4") 1910 x 760 (6'3" x 2'6") 1880 x 760 (6'2" x 2'6")	1 x Double 2030 x 1220 (6'8" x 4'0") 1 x Double 1850 x 1370 (6'1" x 4'6")	1 x Double 2030 x 1475 (6'8" x 4'10") 1 x Double 1980 x 1370 (6'6" x 4'6") 2 x Single Bunk 1730 x 610 (5'8" x 2'0")
Option 2				
M.T.P.L.M	1840kg / 36.2cwt	1825kg / 35.9cwt	1810kg / 35.6cwt	1860kg / 36.6cwt
Mass in Running Order	1643kg / 32.3cwt	1628kg / 32cwt	1613kg / 31.8cwt	1653kg / 32.5cwt
Essential Habitation Equipment	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt
Personal Payload	140kg / 2.8cwt	140kg / 2.8cwt	140kg / 2.8cwt	160kg / 3.1cwt
Options Payload	10kg / 0.2cwt	10kg / 0.2cwt	10kg / 0.2cwt	0kg / 0cwt
Total / Maximum User Payload	197kg / 3.9cwt	197kg / 3.9cwt	197kg / 3.9cwt	207kg / 4.1cwt
Empty Nose Weight	44.5kg / 0.9cwt	55kg / 1.1cwt	76kg / 1.5cwt	39.5kg / 0.8cwt
Maximum Hitch Weight	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt
Awning Measurements (to ground)	1070 cm	1070 cm	1070 cm	1070 cm



TECHNICAL SPECIFICATIONS 2009

MODEL	460/2	520/4	535/4	545/4
Number of Berths	2	4	4	4
Interior Length	4858mm / 15' 11"	5514mm / 18' 1"	5500mm / 18' 1"	5800mm / 19' 0"
Shipping Length	6633mm / 21' 9"	7289mm / 23' 11"	7275mm / 23' 10"	7575mm / 24' 10"
Overall Width	2260mm/7'5"	2260mm/7'5"	2260mm/7'5"	2260mm/7'5"
Overall Height (inc TV Aerial)	2660mm / 8' 9"	2660mm / 8' 9"	2660mm / 8' 9"	2660mm / 8' 9"
Maximum Headroom	1955mm / 6' 5"	1955mm / 6' 5"	1955mm / 6' 5"	1955mm/6'5"
Interior Width	2110mm / 6' 11"	2110mm / 6' 11"	2110mm / 6' 11"	2110mm/6'11"
Wheel Rim	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15
Tyre Size	185 R14 102	195/70 R15 104	195/70 R15 104	195/70 R15 104
Tyre Pressure (at quoted MTPLM)	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar
Bed Sizes mm	2 x Single 1900 x 720 (6'3" x 2'4")	2 x Single 1900 x 720 (6'3" x 2'4") 1 x Single 1795 x 710 (5'11" x 2'4") 1 x Single Bunk 1755 x 610 (5'9" x 2'0")	2 x Single 1680 x 720 (5'6" x 2'4") 1 x Double 1955 x 1430 (6'5" x 4'8")	2 x Single 1550 x 720 (5'1" x 2'4") 1 x Double 1830 x 1370 (6'0" x 4'6")
Option 1				
Bed Sizes mm	1 x Double 2030 x 1475 (6'8" x 4'10")	1 x Double 2030 x 1475 (6'8" x 4'10") 1 x Single 1795 x 710 (5'11" x 2'4") 1 x Single Bunk 1755 x 610 (5'9" x 2'0")	1 x Double 2030 x 1270 (6'8" x 4'2") 1 x Double 1955 x 1430 (6'5" x 4'8")	1 x Double 2030 x 1110 (6'8" x 3'7") 1 x Double 1830 x 1370 (6'0" x 4'6")
Option 2				
M.T.P.L.M	1435kg / 28.2cwt	1600kg / 31.5cwt	1580kg / 31.1cwt	1635kg / 32.2cwt
Mass in Running Order	1281kg / 25.2cwt	1420kg / 28cwt	1392kg / 27.4cwt	1444kg / 28.4cwt
Essential Habitation Equipment	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt
Personal Payload	107kg / 2.1cwt	133kg / 2.6cwt	133kg / 2.6cwt	136kg / 2.7cwt
Options Payload	0kg / 0cwt	0kg / 0cwt	8kg / 0.2cwt	8kg / 0.2cwt
Total / Maximum User Payload	154kg / 3cwt	180kg / 3.5cwt	188kg / 3.7cwt	191kg / 3.8cwt
Empty Nose Weight	46kg / 0.9cwt	48kg / 0.9cwt	65kg / 1.3cwt	56kg / 1.1cwt
Maximum Hitch Weight	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt
Awning Measurements (to ground)	935 cm	1000 cm	999 cm	1029 cm



TECHNICAL SPECIFICATIONS 2009

MODEL	460/2	470/2	520/4	530/4	535/4
Number of Berths	2	2	4	4	4
Interior Length	4858mm / 15' 11"	5000mm / 16' 5"	5514mm / 18' 1"	5487mm / 18' 0"	5500mm / 18' 1"
Shipping Length	6633mm / 21' 9"	6775mm / 22' 3"	7289mm / 23' 11"	7262mm / 23' 10"	7275mm / 23' 10"
Overall Width	2260mm/7'5"	2260mm/7'5"	2260mm/7'5"	2260mm/7'5"	2260mm/7'5"
Overall Height (inc TV Aerial)	2660mm / 8' 9"	2660mm / 8' 9"	2660mm / 8' 9"	2660mm / 8' 9"	2660mm / 8' 9"
Maximum Headroom	1955mm/6'5"	1955mm/6'5"	1955mm/6'5"	1955mm/6'5"	1955mm/6'5"
Interior Width	2110mm/6'11"	2110mm/6'11"	2110mm/6'11"	2110mm/6'11"	2110mm/6'11"
Wheel Rim	5.5J x 14	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15
Tyre Size	185 R14 102	185 R14 102	195/70 R15 104	195/70 R15 104	195/70 R15 104
Tyre Pressure (at quoted MTPLM)	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar
Bed Sizes mm	2 x Single 1900 x 720 (6'3" x 2'4")	2 x Single 1900 x 720 (6'3" x 2'4")	2 x Single 1880 x 720 (6'3" x 2'4") 1 x Single 1795 x 710 (5'11" x 2'4") 1 x Single Bunk 1755 x 610 (5'9" x 2'0")	2 x Single 1880 x 720 (5'6" x 2'4") 1 x Double 1955 x 1430 (6'5" x 4'8")	2 x Single 1680 x 720 (5'6" x 2'4") 1 x Double 1955 x 1430 (6'5" x 4'8")
Option 1					
Bed Sizes mm	1 x Double 2030 x 1475 (6'8" x 4'10")	1 x Double 2030 x 1475 (6'8" x 4'10")	1 x Double 2030 x 1475 (6'8" x 4'10") 1 x Single 1795 x 710 (5'11" x 2'4") 1 x Single Bunk 1755 x 610 (5'9" x 2'0")	1 x Double 2030 x 1270 (6'8" x 4'2") 1 x Double 1820 x 710 (6'0" x 2'4") 1 x Double 1955 x 1430 (6'5" x 4'8")	1 x Double 2030 x 1270 (6'8" x 4'8") 1 x Double 1820 x 710 (6'0" x 2'4") 1 x Double 1955 x 1430 (6'5" x 4'8")
Option 2					
M.T.P.L.M	1420kg / 28cwt	1440kg / 28.3cwt	1595kg / 31.4cwt	1585kg / 31.2cwt	1565kg / 30.8cwt
Mass in Running Order	1263kg / 24.9cwt	1282kg / 25.2cwt	1412kg / 27.8cwt	1394kg / 27.4cwt	1374kg / 27cwt
Essential Habitation Equipment	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt
Personal Payload	107kg / 2.1cwt	108kg / 2.1cwt	133kg / 2.6cwt	133kg / 2.6cwt	133kg / 2.6cwt
Options Payload	3kg / 0.1cwt	3kg / 0.1cwt	3kg / 0.1cwt	11kg / 0.2cwt	11kg / 0.2cwt
Total / Maximum User Payload	157kg / 3.1cwt	158kg / 3.1cwt	183kg / 3.6cwt	191kg / 3.8cwt	191kg / 3.8cwt
Empty Nose Weight	46kg / 0.9cwt	45kg / 0.9cwt	47kg / 0.9cwt	50kg / 1cwt	64kg / 1.3cwt
Maximum Hitch Weight	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt
Awning Measurements (to ground)	935 cm	949 cm	1000 cm	998 cm	999 cm



TECHNICAL SPECIFICATIONS 2009

MODEL	380/2	450/2	520/4	535/4	550/5	560/6	640/6
Number of Berths	2	2	4	4	5	6	6
Interior Length	3973mm / 13' 0"	4675mm / 15' 4"	5428mm / 17' 10"	5500mm / 18' 1"	5620mm / 18' 5"	5575mm / 18' 3"	6171mm / 20' 3"
Shipping Length	5728mm / 18' 10"	6430mm / 21' 1"	7183mm / 23' 7"	7255mm / 23' 10"	7375mm / 24' 2"	7330mm / 24' 1"	7926mm / 26' 0"
Overall Width	2260mm / 7' 5"	2260mm / 7' 5"	2260mm / 7' 5"	2260mm / 7' 5"	2260mm / 7' 5"	2260mm / 7' 5"	2260mm / 7' 5"
Overall Height (inc TV Aerial)	2610mm / 8' 7"	2610mm / 8' 7"	2610mm / 8' 7"	2610mm / 8' 7"	2610mm / 8' 7"	2610mm / 8' 7"	2610mm / 8' 7"
Maximum Headroom	1911mm / 6' 3"	1911mm / 6' 3"	1911mm / 6' 3"	1911mm / 6' 3"	1911mm / 6' 3"	1911mm / 6' 3"	1911mm / 6' 3"
Interior Width	2110mm / 6' 11"	2110mm / 6' 11"	2110mm / 6' 11"	2110mm / 6' 11"	2110mm / 6' 11"	2110mm / 6' 11"	2110mm / 6' 11"
Wheel Rim	5.5J x 14	5.5J x 14	5.5J x 14	5.5J x 14	6.0J x 15	6.0J x 15	5.5J x 14
Tyre Size	175 R14 99	185 R14 102	185 R14 102	185 R14 102	195/70 R15 104	195/70 R15 104	175/65R14 86
Tyre Pressure (at quoted MTPLM)	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	44 psi / 3 bar
Bed Sizes mm	2 x Single 1900 x 720 (6'0" x 2'4")	2 x Single 1830 x 720 (6'0" x 2'4")	2 x Single 1830 x 720 (6'0" x 2'4") 1 x Single 1820 x 710 (6'0" x 2'4") 1 x Single Bunk 1760 x 610 (5'9" x 2'0")	2 x Single 1830 x 720 (6'0" x 2'4") 1 x Double 1955 x 1430 (6'5" x 4'8")	2 x Single 1830 x 720 (6'0" x 2'4") 1 x Double 2030 x 1370 (6'8" x 4'6") 1 x Single Bunk 1830 x 610 (6'0" x 2'0")	2 x Single 1830 x 720 (6'0" x 2'4") Bunks 1820 x 710 (6'0" x 2'4") 1760 x 610 (5'9" x 2'0") 2@ 1750 x 595 (5'9" x 2'0")	2 x Single 1830 x 720 (6'0" x 2'4") Bunks 1820 x 710 (6'0" x 2'4") 1760 x 610 (5'9" x 2'0") 2@ 1750 x 595 (5'9" x 2'0")
Option 1							
Bed Sizes mm	1 x Double 2030 x 1420 (6'8" x 4'8")	1 x Double 2030 x 1420 (6'8" x 4'8")	1 x Double 2030 x 1420 (6'8" x 4'8") 1 x Single 1820 x 710 (6'0" x 2'4") 1 x Single Bunk 1760 x 610 (5'9" x 2'0")	1 x Double 2030 x 1420 (6'8" x 4'8") 1 x Double 1955 x 1430 (6'5" x 4'8")	1 x Double 2030 x 1420 (6'8" x 4'8") 1 x Double 2030 x 1370 (6'8" x 4'6") 1 x Single Bunk 1830 x 610 (6'0" x 2'0")	1 x Double 2030 x 1420 (6'8" x 4'8") Bunks 1820 x 710 (6'0" x 2'4") 1760 x 610 (5'9" x 2'0") 2@ 1750 x 595 (5'9" x 2'0")	1 x Double 2030 x 1420 (6'8" x 4'8") Bunks 1820 x 710 (6'0" x 2'4") 1760 x 610 (5'9" x 2'0") 2@ 1750 x 595 (5'9" x 2'0")
Option 2							
M.T.P.L.M	1200kg / 23.6cwt	1340kg / 26.4cwt	1500kg / 29.5cwt	1480kg / 29.1cwt	1590kg / 31.3cwt	1575kg / 31cwt	1710kg / 33.7cwt
Mass in Running Order	1048kg / 20.6cwt	1181kg / 23.2cwt	1314kg / 25.9cwt	1293kg / 25.5cwt	1392kg / 27.4cwt	1367kg / 26.9cwt	1496kg / 29.4cwt
Essential Habitation Equipment	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt	47kg / 0.9cwt
Personal Payload	98kg / 1.9cwt	105kg / 2.1cwt	132kg / 2.6cwt	133kg / 2.6cwt	144kg / 2.8cwt	154kg / 3cwt	160kg / 3.1cwt
Options Payload	7kg / 0.1cwt	7kg / 0.1cwt	7kg / 0.1cwt	7kg / 0.1cwt	7kg / 0.1cwt	7kg / 0.1cwt	7kg / 0.1cwt
Total / Maximum User Payload	152kg / 3.3cwt	159kg / 3.1cwt	186kg / 3.7cwt	187kg / 3.7cwt	198kg / 3.9cwt	208kg / 4.1cwt	214kg / 4.2cwt
Empty Nose Weight	46kg / 0.9cwt	36kg / 0.7cwt	45kg / 0.9cwt	65kg / 1.3cwt	57kg / 1.1cwt	49kg / 1cwt	60kg / 1.2cwt
Maximum Hitch Weight	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt	100kg / 1.9cwt
Awning Measurements (to ground)	825cm	890cm	965cm	980cm	992cm	988cm	1050cm



Awning dimensions represent the shortest ground to ground awning measurements for 2009 model year Coachman Caravans. We do however **strongly recommend** that you consult your awning supplier before making a purchase as awning manufacturers have different methods of sizing their products.